

## Homework sheet 6, due 13 January 2022 at 13:30

Submit your homework (pdf and code, if any) by encrypted and signed email to all TAs. Do not forget to attach your public key and the public key of anybody you put in cc. Make sure to have different members of your group handle the submission.

1. Alice is a web merchant offering encrypted connections using semi-static DH in  $\mathbb{F}_{103}^*$  in the subgroup of order  $\ell = 51$  generated by 2.

For this exercise you should not use your computer for more functions than a pocket calculator offers you; in particular make sure to give full details when computing inverses and exponentiations and document all steps.

- (a) Verify that 2 has order 51, justify your computation and try to use not too many multiplications and squarings. 2 points

- (b) Alice's public key is  $h_A = 30$ . Use the baby-step giant-step algorithm to compute an integer  $a$  between 0 and 50 so that  $g^a = h_A$ , i.e. compute the discrete logarithm of Alice's key. Solutions using brute-force search for  $a$  will not be accepted. Make sure to verify your result by computing  $g^a$ . // Remember that BSGS expects you to make a table of all baby steps so those should be written out as well as any giant step you check against the table. The table is small enough, you need not sort it. 7 points

2. NSA cryptographer Rick Proto noticed independently of Diffie and Hellman that exponentiation in finite fields is easy while computing discrete logarithms can be hard. The scheme he came up with requires several interactions between the sender and receiver.

The system parameter is a large prime  $p$ .

To send message  $m < p$  to user Bob, Alice chooses a random integer  $A < p$  with  $\gcd(A, p-1) = 1$  and computes  $a \equiv A^{-1} \pmod{p-1}$ . She then computes  $c_1 \equiv m^A \pmod{p}$  and sends  $c_1$  to Bob.

Bob chooses a random integer  $B < p$  with  $\gcd(B, p-1) = 1$  and computes  $b \equiv B^{-1} \pmod{p-1}$ . Bob then computes  $c_2 \equiv c_1^B \pmod{p}$  and sends  $c_2$  to Alice.

Alice then computes  $c_3 \equiv c_2^a \pmod{p}$  and sends  $c_3$  to Bob.

Bob decrypts the message by computing  $m' \equiv c_3^b \pmod{p}$ .

- (a) Let  $p = 23$ . Execute one run of the protocol in which Alice wants to send  $m = 2$  and picks  $A = 5$  and computes  $a = 5^{-1} \equiv 9 \pmod{22}$ , and Bob picks  $B = 3$  and computes  $b = 3^{-1} \equiv 15 \pmod{22}$ . Compute  $c_1, c_2, c_3$ , and  $m'$ . 5 points

- (b) Explain why the system works, i.e., explain why  $m' = m$ . 3 points

- (c) Attacker Eve observes the conversations between Alice and Bob and obtains  $c_1, c_2$ , and  $c_3$ ; she also knows the system parameter  $p$ . Assume that Eve can compute discrete logarithms in  $\mathbb{F}_p^*$ . Show how she can obtain  $m$  from the observed ciphertexts.

Note that you need to show where to find a DLP in this system and how to use the solution.

3 points
----------